



## Features

- Industrial-grade 15" XGA LCD panel with 50k backlight lifetime
- High precision 5-wires resistive touch, EETI controller
- Intel® Celeron® J1900 quad-core 2.0 GHz processor
- 1 x DDR3 SDRAM max.8GB, 1 x mSATA SSD
- SP13 I/O ports: 2 x LAN / 2 x USB / 1 x COM
- Full device IP67 with Strong aluminum alloy casing
- Wide Operating Temperature -20°C to 70°C
- 12V to 24V DC Wide Range Power Input

## Specifications

System	
CPU	Intel® Bay Trail Celeron J1900 Quad-core 2.0GHz
L2 Cache	2MB
TDP	10W
System Chipset	Integrated with Intel® SoC
Memory	1 x DDR3L 1333MHz 4GB, Up to 8GB
Harddisk	1 x mSATA 128G SSD / (250G / 500G / 1TB SSD)
Graphics	Intel HD Graphics
Network	Intel® 226-V GbE LAN
Audio	Realtek ACL662 Audio controller
Watchdog Timer	Software Programmable Supports 1~255 sec. System Reset
Operation System	Windows 7 / 8 / 10 , Linux, Ubuntu
I/O	
VIDEO	1 x H-DMI ( Optional )
Ethernet	2 x SP13 Waterproof Giga LAN RJ45 Connector
USB	2 x SP13 Waterproof Connector For USB2.0
COM	1 x SP13 Waterproof Connector For COM
Wireless Network	Optional ( WiFi / Bluetooth / 4G )
Other I/O Interface	1 x Power Switch
Expansion	
mPCe	1 x mPCe ( Wifi+BT+4G )
SIM Socket	1x SIM Socket
Display	
LCD Size	15" ( 4:3 )
Resolution	1024 x 768
Brightness (cd/m <sup>2</sup> )	350 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Backlight MTBF	50000 hrs
Viewing Angle	89 / 89 / 89 / 89 (CR≥10) ( L / R / U / D )
Touch screen	
Touch Type	5 wire Resistive touch
Surface Hardness	≥3H

Power	
Power Adapter	1 x Optional AC/DC 12V/5A , 60W
Power Input	2-Pin SP13 Power Input 12~24VDC
Power Consumption	≤35W
Physical	
Material	Aluminum Alloy Shell
Mounting	Stand / Wall / VESA
Dimension (W x H x D)	362 x 285 x 42 mm
Packing Size	460 x 180 x 400 mm
Weight (Net)	4.0 kg
Environment	
Operating Temperature	-20~70°C ( -4~158°F )
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	IP67 / IP69K
EMC	CE, FCC, Class A, ROHS

### Dimension & I/O

**Product Dimensions: 362 x 285 x 42 mm (14.25 x 11.22 x 1.65 in)**

**I / O Definition:**

A: Power Switch	B: Breather Valve
C: COM ( optional )	D: USB ( optional )
E: USB ( optional )	F: LAN ( optional )
G: LAN ( optional )	H: DC 12V-24V

### Ordering info

Available models	Description
WPC-J015SAR	15" Fanless Waterproof Industrial PC Intel® Celeron J1900 2.0GHz Processor With Resistive touch

### Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
2 x SP13 Waterproof USB Cable 2M
1 x SP13 Waterproof COM Cable 2M
2 x SP13 Waterproof LAN Cable 2M