



## Features

- Industrial-grade 17" SXGA LCD panel with 50k backlight lifetime
- High precision 5-wires resistive touch, EETI controller
- Intel® Celeron® J6412 quad-core 2.0 GHz processor
- 1 x DDR4 SDRAM, max.32GB, 1 x M.2 2280 ( NVMe or SATA ) SSD
- M12 I/O ports: 2 x LAN / 2 x USB / 1 x COM
- Full device IP67/IP69K with Stainless Steel SUS304/316 construction
- Support TPM2.0 hardware security
- Wide Operating Temperature -20°C to 70°C
- 9V to 36V DC Wide Range Power Input, Supporting OVP / OCP / RPP

## Specifications

System	
CPU	Intel® Elkhart Lake Celeron J6412 Quad-core 2.0GHz
L2 Cache	1.5MB
TDP	10W
System Chipset	Integrated with Intel® SoC
Memory	1 x DDR4L 3200MHz 4GB, MAX 32GB
Harddisk	1 x M.2 120G SSD ( 250G / 500G / 1TB SSD)
Graphics	Intel® UHD Graphics for 10th Gen Intel® Processors
Network	Intel® 226-V GbE LAN
Audio	Realtek ALC897 Audio controller
TPM	TPM 2.0
Operation System	Windows 10 / 11, Linux, Ubuntu
I/O	
VIDEO	1 x H-DMI ( Optional )
Ethernet	2 x M12 Waterproof Giga LAN RJ45 Connector
USB	2 x M12 Waterproof Connector For USB2.0
COM	1 x M12 Waterproof Connector For COM
Wireless Network	Optional ( WiFi / Bluetooth / 4G / 5G )
Other I/O Interface	1 x Power Switch
Expansion	
M.2	1*M.2 ( Key-E, 2230, PCIe+USB, Wifi+BT)
	1*M.2 ( Key-B, 3042/3052, PCIe/ USB 3.0+USB2.0, 4G/5G )
	1*M.2 ( Key-M, 2280, NVMe/ SATA, SSD )
SIM Socket	1x SIM Socket
Display	
LCD Size	17" ( 5:4 )
Resolution	1280 x 1024
Brightness (cd/m <sup>2</sup> )	400 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Backlight MTBF	50000 hrs
Viewing Angle	80 / 80 / 70 / 70 (CR≥10) ( L / R / U / D )
Touch screen	
Touch Type	5 Wire Resistive touch
Surface Hardness	≥3H

Power	
Power Input	1 x M12 Waterproof Connector For 9V~36V DC
Power Protection	OVP (Over Voltage Protection)   OCP (Over Current Protection)   RPP (Reverse Polarity Protection)
Power Consumption	≤35W
Physical	
Material	Inox / SUS304 / SUS316
Mounting	Stand / Wall / VESA / Yoke
Dimension (W x H x D)	392 x 325 x 56 mm
Packing Size	500 x 180 x 450 mm
Weight (Net)	7.8 kg
Environment	
Operating Temperature	-20~70°C (-4~158°F)
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	IP66 / IP69K
EMC	CE, FCC, Class A, ROHS

### Dimension & I/O

**I / O Definition:**

A: DC 9V~36V	B: LAN (optional)
C: LAN (optional)	D: USB (optional)
E: USB (optional)	F: COM (optional)
G: Breather Valve	H: Power Switch

**Product Dimensions: 392.6 x 325 x 55 mm (15.45 x 12.79 x 2.17 in )**

### Ordering info

Available models	Description
WPC-C017SCR	17" Fanless Waterproof Industrial PC Intel® Celeron J6412 2.0GHz Processor With Resistive touch

### Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
2 x M12 Waterproof USB Cable 2M
1 x M12 Waterproof COM Cable 2M
2 x M12 Waterproof LAN Cable 2M