



Features

- Industrial-grade 23.8" FHD LCD panel with 30k backlight lifetime
- Optical bonding PCAP multipoint touch screen
- Intel® Celeron® J1900 quad-core 2.0 GHz processor
- 1 x DDR3 SDRAM max.8GB, 1 x mSATA SSD
- M12 I/O ports: 2 x LAN / 2 x USB / 1 x COM
- Full device IP66/IP69K with Stainless Steel SUS304/316 construction
- Wide Operating Temperature -20°C to 70°C
- 12V to 24V DC Wide Range Power Input

Specifications

System	
CPU	Intel® Bay Trail Celeron J1900 Quad-core 2.0GHz
L2 Cache	2MB
TDP	10W
System Chipset	Integrated with Intel® SoC
Memory	1 x DDR3L 1333MHz 4GB, Up to 8GB
Harddisk	1 x mSATA 128G SSD / (250G / 500G / 1TB SSD)
Graphics	Intel HD Graphics
Network	Intel® 226-V GbE LAN
Audio	Realtek ACL662 Audio controller
Watchdog Timer	Software Programmable Supports 1~255 sec. System Reset
Operation System	Windows 7 / 8 / 10 , Linux, Ubuntu
I/O	
VIDEO	1 x H-DMI (Optional)
Ethernet	2 x M12 Waterproof Giga LAN RJ45 Connector
USB	2 x M12 Waterproof Connector For USB2.0
COM	1 x M12 Waterproof Connector For COM
Wireless Network	Optional (WiFi / Bluetooth / 4G)
Other I/O Interface	1 x Power Switch
Expansion	
mPCe	1 x mPCe (Wifi+BT+4G)
SIM Socket	1x SIM Socket
Display	
LCD Size	23.8" (16:9)
Resolution	1920 x 1080 (FHD)
Brightness (cd/m ²)	350 cd/m ²
Contrast Ratio	1000:1
Backlight MTBF	30000 hrs
Viewing Angle	89 / 89 / 89 / 89 (CR≥10) (L / R / U / D)
Touch screen	
Touch Type	Optical bonding PCAP Touch
Surface Hardness	≥7H

Power	
Power Adapter	1 x Optional AC/DC 12V/5A , 60W
Power Input	2-Pin M12 Power Input 12~24VDC
Power Consumption	≤40W
Physical	
Material	Inox / SUS304 / SUS316
Mounting	Stand / Wall / VESA / Yoke
Dimension (W x H x D)	583 x 353 x 56 mm
Packing Size	730 x 190 x 530 mm
Weight (Net)	11.8 KG
Environment	
Operating Temperature	-20~70°C (-4~158°F)
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	IP66 / IP69K
EMC	CE, FCC, Class A, ROHS

Dimension & I/O

Product Dimensions: 583 x 352.5 x 56 mm (22.95 x 13.88 x 2.20 in)

I / O Definition:

A: DC 12V~24V	B: LAN (optional)
C: LAN (optional)	D: USB (optional)
E: USB (optional)	F: COM (optional)
G: Breather Valve	H: Power Button

Ordering info

Available models	Description
WPC-J024WCC	23.8" Fanless Waterproof Industrial PC Intel® Celeron J1900 2.0GHz Processor With Capcice touch

Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
2 x M12 Waterproof USB Cable 2M
1 x M12 Waterproof COM Cable 2M
2 x M12 Waterproof LAN Cable 2M