



## Features

- Industrial-grade 17" SXGA LCD panel with 50k backlight lifetime
- Optical bonding PCAP multipoint touch screen
- IP66 grade aluminum alloy front panel
- Intel® Core™ Ultra5 225U 1.3 / 255U 1.7 GHz processor
- 2 x DDR5 SDRAM, max.96GB, 1 x M.2 2280 NVMe SSD
- 2 x Intel® 226-V 2.5GbE Ethernet, support WoL and PXE
- 2 x RS232/422/485, RS485 support automatic flow control
- Supports TPM2.0 security encryption and Intel vPro® Essentials
- Supports embedded / VESA 100mm x 100mm mounting holes
- 9V to 36V DC Wide Range Power Input, Supporting OVP / OCP / RPP

## Specifications

System	
CPU	Intel® Core™ Ultra5 225U 1.3GHz   Intel® Core™ Ultra5 255U 1.7GHz
TDP	15W
Core / Tread	12C / 2P+8E
L3 Cache	12MB
GPU	Intel® Graphics 2.0 GHz , 8TOPS
NPU	Intel® AI Boost, 12TOPS
Chipset	Integrated With Intel® SoC
BIOS	AMI UEFI
Memory	2 x DDR5 6400MHz 16GB, Up to 96GB, Non-ECC
Harddisk	1 x M.2 256G SSD ( 500G / 1TB SSD )
Audio	Realtek ALC897 Audio controller
TPM	TPM 2.0
Watchdog Timer	255 Timer Levels, Set up by Software
Operation System	Windows 10 / 11, Linux, Ubuntu
I / O	
VIDEO	2 x DP
Ethernet	2 x Intel® I226V, 2.5GbE
USB	4 x USB 3.2 Gen 2 x 2
COM	2 x RS-232 / 422 / 485 ( Adjustable through BIOS )
Audio	1x Audio_out & Mic_in
Wireless Network	Optional ( WiFi / Bluetooth / 4G / 5G )
Expansion	
M.2	1*M.2 ( Key-E, 2230, PCIe+USB, Wifi+BT )
	1*M.2 ( Key-B, 3042/3052, PCIe/ USB 3.0+USB2.0, 4G/5G )
	1*M.2 ( Key-M, 2280, NVMe/ SATA, SSD )
SIM Socket	1x SIM Socket
Display	
LCD Size	17" ( 5:4 )
Resolution	1280 x 1024
Brightness (cd/m²)	400 cd/m²
Contrast Ratio	1000:1
Backlight MTBF	50,000 hrs ( LED Backlight )
Viewing Angle	80 / 80 / 70 / 70 (CR≥10) ( L / R / U / D )

Touch screen	
Touch Type	Optical bonding PCAP Touch
Surface Hardness	≥7H
Power	
Power Adapter	1 x Optional AC/DC 12V/5A , 60W
Power Mode	Support AT, ATX Mode
Power Input	9~36VDC, 2-Pin Terminal Block Connector with Power Input
Power Protection	OVP ( Over Voltage Protection )   OCP ( Over Current Protection )   RPP ( Reverse Polarity Protection )
Power Consumption	≤45W
Physical	
Material	Aluminum alloy panel, anodized treatment
Mounting	Stand / Wall / VESA / Panel
Dimension (W x H x D)	395 x 327 x 65 mm
Cut-out Size	381 x 313 mm
Packing Size	500 x 180 x 450 mm
Weight (Net)	5.1 KG
Environment	
Operating Temperature	-20~70°C ( -4~158°F )
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	Front Panel IP66
EMC	CE, FCC, KC , Class A, ROHS , IEC, EN 62368-1

### Dimension & I/O

The technical drawings include:

- Front View:** Shows the overall dimensions of the panel: 394.60 mm width and 327.00 mm height. A dashed line indicates the cutout size of 381 mm x 313 mm.
- Side View:** Shows the panel's thickness of 8.00 mm and the mounting bracket height of 65.00 mm.
- Back View:** Shows the internal layout of the I/O ports, with a 100.00 mm spacing between the two columns of ports.
- I/O Definition:**
  - A: Power Button
  - B: AT/ATX
  - C: DC 9V~36V
  - D: 2 x LAN
  - E: 2 x DP
  - F: 2 x USB 3.2
  - G: 2 x USB 3.2
  - H: Audio
  - I: COM1:RS-232/422/485
  - J: COM2:RS-232/422/485

**Panel Cutout Dimensions: 381 x 313 mm ( 15 x 12.32 in )**

## Ordering info

Available models		Description
	PPC-5017SAC-15th-2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 225U 1.3GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS-232 / 422 / 485
	PPC-7017SAC-15th-2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 255U 1.7GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS-232 / 422 / 485
	PPC-5017SAC-15th-4C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 225U 1.3GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS232/RS422/RS485, 2 x RS232
	PPC-7017SAC-15th-4C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 255U 1.7GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS232/RS422/RS485, 2 x RS232
	PPC-5017SAC-15th-4L	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 225U 1.3GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 4 x Intel® I226V, 2.5GbE
	PPC-7017SAC-15th-4L	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 255U 1.7GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 4 x Intel® I226V, 2.5GbE
	PPC-5017SAC-15th-8D+2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 225U 1.3GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS232/RS422/RS485, 8 x Digital I/O (4in/4out)
	PPC-7017SAC-15th-8D+2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 255U 1.7GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x RS232/RS422/RS485, 8 x Digital I/O (4in/4out)
	PPC-5017SAC-15th-2L+2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 225U 1.3GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x LAN, 2 x RS232/RS422/RS485
	PPC-7017SAC-15th-2L+2C	17" Fanless Industrial Panel PC Intel® Core™ Ultra5 255U 1.7GHz Processor With Optical bonding PCAP Touch, 2 x DP / 2 x Intel® I226V, 2.5GbE / 4 x USB 3.2 Gen 2 x 2 / 2 x LAN, 2 x RS232/RS422/RS485

## Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
1 x Power cable & plug
8 x Panel mount metal clips